

# NTE/NTG

Stacked unit for  
semi-commercial  
laundry applications



## FEATURES

- Freestanding, can be installed on any floor and any level
- Double capacity in same floor space
- Top, front and side panels standard available in white
- Stainless steel outer and inner drum
- Redesigned soap box with 4 compartments
- 440 G-force extraction
  - removes more moisture
  - minimizes drying times and utility costs
- 6 wash programs with possibility of programming cycle modifier options
  - added prewash
  - extra wash time
  - extra rinse
- 5 drying programs

## OPTIONS

- Top, front and side panels in stainless steel
- Coin-operated version for vended laundry applications

# DIMENSIONS & SPECIFICATIONS

## STACKED UNIT FOR SEMI-COMMERCIAL LAUNDRY APPLICATIONS

Type		NTE	NTG
Capacity			
Drum volume washer	l	96,8	96,8
Drum volume dryer	l	201	201
Motor			
Power motor washer	kW	0,67	0,67
Power motor dryer	kW	0,25	0,25
Connections			
Gas inlet connection	mm	-	9,5
Gas consumption	BTU/hr	-	25.000
Available electrical requirements		120/240/60/1 - 30A 120/208/60/1 - 30A 230/50/1 - 30A 220/60/1 - 30A	120/60/1 - 15A 220/60/1 - 10A 230/50/1 - 10A
Dimensions (H x W x D)	mm	1986 x 683 x 704	1986 x 683 x 704
Net weight	kg	177	177
Transport data			
Bruto weight	kg	193	193
Shipping dimensions (H x W x D)	mm	2032 x 737 x 832	2032 x 737 x 832
Packed volume	m <sup>3</sup>	1,25	1,25

**Electric Models**

SWD1023N\_SVG

- A \*1678 mm
- B \*1447 mm
- C 597 mm
- D 213 mm
- E 610 mm
- F 203 mm
- G 391 mm
- H \*938 mm
- I \*368 mm
- J \*813 mm
- K 683 mm
- L \*1986 mm
- M \*1184 mm
- N 52 mm
- O 704 mm
- P 38 mm
- Q \*333 mm

\* With leveling legs turned into base.

**Gas Models**

SWD1024N\_SVG

- A \*1678 mm
- B \*1447 mm
- C 597 mm
- D 213 mm
- E 610 mm
- F 203 mm
- G 391 mm
- H 59 mm
- I \*938 mm
- J \*368 mm
- K \*1140 mm
- L \*813 mm
- M 683 mm
- N \*1986 mm
- O \*1184 mm
- P 52 mm
- Q \*704 mm
- R 38 mm
- S \*333 mm

\* With leveling legs turned into base.