



MICROPROCESSOR CONTROLLED

Microprocessor controlled evacuating drying cabinet. Illuminated and with two automatic and three manually, time controlled programs. The automatic programs are turned off when the laundry is dry.

TS 6 MP is delivered in one piece, ready to use. TS 9 MP is delivered as flat pack for delivery reasons and must be assembled before use.

Choose between automatic or normal drying programs.



Standard equipment

- Microprocessor controlled evacuating drying cabinet with double doors.
- Effective lights.
- TS 6 MP in grey "Skinplate"
- TS 9 MP in gray aluzink steel plate.
- Stable swinging, hanging rails.
- The program panel is placed on the left side, at comfortable working height (TS 6 MP).
- Recirculation system, hot air.
- Adjustable feet, 4 pcs.

Microprocessor

- Two automatic drying programs; "cupboard dry" and "ironing dry."
- Three manually time controlled drying programs; 30°, 50° and 70 °C.
- The automatic programs ends when set residual moisture is reached.
- Possible to upgrade.
- Automatic "cool-down" the last 10 minutes of the drying process.

Optional extras

- Drying frame to be placed on the door with hooks for small garments like gloves, socks etc. Part No 131011.
- Single bar.

Illuminated drying cabinet.



Main specifications

| | TS 6 MP | TS 9 MP |
|----------------------------|-----------------|------------------|
| Loading capacity, kg/lbs | 6-8/13,22-17,63 | 8-10/17,63-22,04 |
| Drying capacity, g/min * | 67 | 67 |
| Heating effect, KW | 6,0 | 9,0 |
| Total effect, KW | 6,3 | 9,3 |
| Consumption data | | |
| Drying time, max, min | 90 | 90 |
| Energy consumption/kg, kWh | 0,8 | 0,8 |
| Part No | 131020 | 131022 |

* Valid for 6 kgs of cotton with a moisture retention of 55%.



goldsolutions - 328473 - Illerødvej - 1st, 4166-37009 - Fax: 45 33-379647
www.goldsolutions.dk | info@goldsolutions.dk

TS 6 MP - TS 9 MP



Technical specification



TS 6 MP - TS 9 MP

| | TS 6 MP | TS 9 MP |
|--|-------------------|------------|
| Electrical connections | | |
| Electrical connection* | 3-N, 400 V, 50 Hz | |
| Fuse, A | 10 | 16 |
| Total effect, kW | 6,3 | 9,3 |
| Heating elements, kW | 6,0 | 9,0 |
| Air connections | | |
| Outlet exhaust, ø mm/Inch | 125/4,92 | 125/4,92 |
| Outlet air flow, m ³ /h | 170 | 170 |
| Pressure drop, max Pa | 80 | 80 |
| Sound level | | |
| Airborne sound level, dB(A) | 50 | 50 |
| Shipping data | | |
| Net, kg/lbs | 145/319,67 | 165/363,76 |
| Crated, kg/lbs | 20/44,09 | 35/77,16 |
| Shipping data net, kg/lbs | 165/363,76 | 200/440,92 |
| Shipping volume, m ³ | 1,85 | 1,90 |
| Optional extras | | |
| Air exchanger 1 vert., 125 mm/4,92 inch | 141009 | 141009 |
| Air exchanger 2 vert., 160 mm/6,3 inch | 141018 | 141018 |
| Dimensions | | |
| Width, mm/Inch | 1200/47,24 | 1700/66,92 |
| Depth, mm/Inch | 690/26,77 | 750/29,52 |
| Height, mm/Inch | 1930/75,98 | 2090/81,89 |

* Other voltage on request.



paukenslag 1 - 3286TD - Klaaswaal = tel: 0186-576050 - Fax: 0186-575047
www.laundrysolutions.nl - info@laundrysolutions.nl