



HYDRO EXTRACTOR IN STAINLESS STEEL



Hydro Extractor is a tough, silent machine built in stainless steel throughout. This is the Hydro Extractor for launderettes, laundries, nursing homes and apartment buildings. The equipment can be prepared for coin operation.

New construction

A new construction of the locking device makes the Extractor even better equipped for heavy use. The locking device is now placed in the front of the lid, which makes it more stable and the Hydro Extractor even safer to operate.

C 46 ER has a strong, fixed marine construction of motor and drum.

C 46 ES/C 66 ES has an elastic suspension of the motor and drum. Therefor suitable for installations in places where vibrations and noise can be a problem.

Safety

The recessed safety lid cannot be opened while the machine is in operation. It is impossible to start the machine with the lid open. Push the start/stop button to open the lid.

Standard

- Solid construction.
- Designed for continuous use.
- Stainless steel throughout.
- New, better locking device.
- Low noise level.



Main specifications

	C 46 ER/ES	C 66 ES
Capacity, kg/lbs	6-8 / 14-18	12-14 / 26-30
Drum volume, l/cu ft	38 / 1,34	60 / 2,12
Extraction 50 Hz, rpm	1400	1400
Extraction 60 Hz, rpm	1650	1650
G-factor 50 Hz	416	622
G-factor 60 Hz	643	896
Consumption data		
Time / extraction, min	4	4
Energy consumption/extraction, kWh	0,04	0,06
Part No C 46 ER	111006	
Part No C 46/66 ES	111008	111011



Paukenslag 1 - 3286 TD - Klaaswaal - tel: 0186-576050 - fax: 0186-575047
www.laundrysolutions.nl - info@laundrysolutions.nl

C 46 ER/ES - C 66 ES



Technical specification



C 46 ER/ES - C 66 ES

	C 46 ER/ES	C 66 ES
Electrical connections		
Electrical connection*	3N, 400V 50 Hz	
Fuse, A	10	10
Motor effect, kW	0,33	0,45
Drain		
Drain, Ø mm/Inch	75/2,95	75/2,95
Floor requirements		
Frequency of the dynamic force, Hz	24	24
Max floor load at extraction, kN	1,0-1,1	1,4
Sound level		
Airborne sound level, dB(A)	70	70
Shipping data		
Net, kg/lbs	75/165,34	130/286,60
Crated, kg/lbs	10/22,04	10/22,04
Shipping data net, kg/lbs	85/187,39	140/308,64
Shipping volume, m ³	0,45	0,75
Optional extras		
	-	-
Dimensions		
Width, mm/Inch	540/21,25	700/27,55
Depth, mm/Inch	690/26,77	890/32,67
Height, mm/Inch	890/32,67	890/32,67

* Other voltage on request.



Paukenslag 1 - 3286 TD - Klaaswaal - tel: 0186-576050 - fax: 0186-575047
www.laundrysolutions.nl - info@laundrysolutions.nl